laservision

Articlenumber: BC1F1P011401
GTIN: 4050369083882
Unit: 1
Weight incl. packaging 2,40 kg
Weight excl. packaging: 2,40 kg

Highlights

The multilayer laser safety curtain BC1.F1P01.1401 with (W x H) 450 x 2000 mm can be hung up via an eyelet tape on the top side. A Velcro/fluff tape is sewn on to connect several panels. The curtain is certified according to EN 60825-4 and tested according to EN 12254.

COLOUR:	silver grey
PROPERTIES:	both-sides usable
PROTECTION CLASS / NORM:	EN 60825, EN 12254
PROTECTION RANGE:	near infrared, Infrared, visible, ultraviolett

WAVELENGTH	OD	OPERATING MODE / TESTED PROTECTION LEVEL
180 - 315	–	D AB8 + IR AB3 + M AB6Y
>315 - 1050	–	D AB7 + I AB8 + R AB7Y + M AB8Y
>1050 - 1400	–	D AB6 + I AB8 + R AB7Y + M AB8Y
>1400 - 20000	–	DIM AB4 + R AB3Y

DIN EN 60825-4

1070nm | 3,85 MW/m^2 | T2 | t_{max} = 200s

LASERVISION GmbH | Würzburger Str. 152, D-90766 Fürth | **T** +49 911 9736 8100 | **E** info@lvg.com | **I** uvex-laservision.de