

laservision

Roll-Up



Articlenumber: BC3F1P011RU1
GTIN: 4050369018297
Unit: 1 Stück
Weight incl. packaging 4,05 kg

Highlights

The roll-up system is characterized by an easy and quick to set up stand. This is covered with the single-layer laser protection curtain BC3.F1P01.1RU1. An area of (W x H) 900 x 2000 mm is covered. To connect several systems, Velcro strips are provided at the edges and the connector BC3.F1P01.1274 is required. The curtain is certified according to EN 12254.

| | |
|---------------------------------|-----------------------------------------------|
| COLOUR: | silver grey |
| PROPERTIES: | Lightweight, single-sided usable |
| PROTECTION CLASS / NORM: | EN 12254 |
| PROTECTION RANGE: | near infrared, Infrared, visible, ultraviolet |

| WAVELENGTH | OD | OPERATING MODE / TESTED PROTECTION LEVEL |
|---------------|--------|------------------------------------------|
| 180 - 315 | (OD5+) | D AB5 + IR AB3 + M AB5Y |
| >315 - 1050 | (OD5+) | DIRM AB5 |
| >1050 - 1400 | (OD5+) | DIRM AB5 |
| >1400 - 20000 | (OD3+) | DI AB3 + R AB3Y + M AB4 |