laservision

laser safety spectacle F42P1L10

Articlenumber: F42P1L101001
GTIN: 4050369050051
Unit: 1 Stück
Weight incl. packaging 0,24 kg
Weight excl. packaging: 0,05 kg

Highlights

- Full Protection (LB) for Nd:YAG, SHG, THG incl. pump diodes
- DIRM LB4 protection level for 532nm DIRM LB6 for 355nm
- Fluorescence effect for alignment
- As OTG in the F18/F22 frame available

The laser safety spectacle F42.P1L10.1001 with disinfectable folding brackets, a new quick release system and cold-forming temple ends has a daylight transmission of approx. 40%. The laser safety is characterized with very high protection against current laser pointer within the blue, green and red range. It provides full protection acc. EN 207 and features M-ratings within the complete range from 180 – 1070nm. It can also be worn as overglasses via prescription lenses. The eyewear comes in a sustainably produced hexagonal cardboard box, along with a microfiber pouch and a cord to hang the goggles on. For cleaning the laser safety goggle, laservision recommends the professional cleaning station (A99CLSTA1300).

Color view



Transmission der Signalfarben nach DIN EN 172 //
transmission of signal colours acc. to EN 172

Filtercurve



Transmissions- und OD-Kurve //
transmission and OD curve

COATING:	no coating
FILTER:	P1L10
FILTER COLOUR:	Orange
FILTER MATERIAL:	Plastic
FILTER TECHNOLOGY:	Absorption filter
FILTER THICKNESS:	ca. 2mm
FRAME:	F42
FRAME TYPE:	OTG with temples
PROPERTIES:	Quick Release, Lightweight, M-protection rating, kaltverformbare Bügelenden, desinfizierbar
PROTECTION CLASS / NORM:	EN 207 full protection
PROTECTION RANGE:	near infrared, visible, ultraviolett
VLT (APPROX.):	40%
VISUAL BRIGHTNESS:	Very good
COLOUR RECOGNITION:	Limited

LASERVISION GmbH & Co.KG | Würzburger Str. 152, D-90766 Fürth | **T** +49 911 9736 8100 | **E** info@lvg.com | **I** uvex-laservision.de

laser safety spectacle F42P1L10

WAVELENGTH	OD	OPERATING MODE / TESTED PROTECTION LEVEL
180 - 315	(OD8+)	D LB8 + IR LB4 + M LB6
>315 - 500	(OD6+)	DIRM LB6
>500 - 532	(OD4+)	DIRM LB4
800 - <975	(OD2+)	DIRM LB2
975 - 1070	(OD4+)	DIRM LB4

LASERVISION GmbH & Co.KG | Würzburger Str. 152, D-90766 Fürth | **T** +49 911 9736 8100 | **E** info@lvg.com | **I** uvex-laservision.de