


laservision

laser safety spectacle R14T1Q06F




Articlenumber: R14T1Q061002
GTIN: 4050369050808
Unit: 1 Stück
Weight incl. packaging 0,65 kg

Color view



Transmission der Signalfarben nach DIN EN 172 //
transmission of signal colours acc. to EN 172

Filtercurve



Transmissions- und OD-Kurve //
transmission and OD curve

Highlights

- Protection Levels acc. to EN 207
- M-Protection in the range of 180-315nm and 620-25,000nm
- Application: Ti_SA, OPO's, USP-lasers and super continuum laser
- 2 different frame styles: [R01](#), [R14](#)
- Different wearing options

The laservision laser safety goggle R14.T1Q06.1002 with a foam frame (F), provides full- protection within the full range between VIS- and the IR-spectral area (620nm - 11,500nm). The OTG goggle with turquoise-green filters can be worn over average large correction glasses. The exchangeable clip frame with foam lends this OTG goggles a unique and good wearing comfort. The laser safety goggle comes with a metal box, which can also be used as a storage box.

COATING:	no coating
CUSHION:	Soft foam (F)
FILTER:	T1Q06
FILTER COLOUR:	Turquoise, Green
FILTER CURVATURE:	Flat filter
FILTER MATERIAL:	Mineral glass
FILTER TECHNOLOGY:	Absorption filter
FILTER THICKNESS:	ca. 11-12mm
FRAME:	R14
FRAME TYPE:	Goggle with strap
PROPERTIES:	Neutral glass lamination
PROTECTION CLASS / NORM:	EN 207 full protection
PROTECTION RANGE:	near infrared, Infrared, visible
VLT (APPROX.):	25%
VISUAL BRIGHTNESS:	Limited
COLOUR RECOGNITION:	Limited

laser safety spectacle R14T1Q06F

WAVELENGTH	OD	OPERATING MODE / TESTED PROTECTION LEVEL
180 - 310	(OD10+)	D LB10 + IR LB4 + M LB6Y
>310 - 315	(OD9+)	D LB9 + IR LB4 + M LB6Y
620 - <680	(OD2+)	DIRM LB2
680 - <690	(OD7+)	DIRM LB6
690 - <750	(OD10+)	D LB7 + IRM LB8
750 - 1400	(OD10+)	D LB7 + IM LB9 + R LB8
>1400 - 3500	(OD5+)	DIM LB5 + R LB4
>3500 - 25000	(OD10+)	DI LB5 + R LB3Y + M LB6Y