

laser safety spectacle R17T1E02




Artikelnr.: R17T1E021001

GTIN: 4050369003729

Unit: 1 Stück


Weight incl. packaging 0,47 kg

Color view



Transmission der Signalfarben nach DIN EN 172 //
transmission of signal colours acc. to EN 172

Filtercurve



Transmissions- und OD-Kurve //
transmission and OD curve

Highlights

- Protection Levels acc. to EN 207
- Application: Nd:YAG Laser at 266/355 or 532nm
- 3 different frame styles available: [R01](#), [R14](#) and [R17](#)
- restricted colour recognition and 40% VLT
- 3 different wearing options
- as cabin window available up to 210x297mm

The laservision laser safety eyewear R17.T1E02.1001 provides high protection ratings within the UV- and VIS-spectral area (180-532nm). The full-protection spectacle without additional coating can be combined with an Rx- corrective insert. The external reinforced spectacle with orange filters offers a good view field. The spectacle is delivered in a metal box, which can also be used as a storage box. Within the scope of delivery is also a holding band.

COATING:	no coating
CUSHION:	No cushion
FILTER:	T1E02
FILTER COLOUR:	Orange
FILTER CURVATURE:	Flat filter
FILTER MATERIAL:	Mineral glass
FILTER TECHNOLOGY:	Absorption filter
FILTER THICKNESS:	ca. 5mm
FRAME:	R17
FRAME TYPE:	Spectacle with Rx insert option
PROPERTIES:	Neutral glass lamination, Adjustable temples
PROTECTION CLASS / NORM:	EN 207 full protection
PROTECTION RANGE:	visible, ultraviolet
VLT (APPROX.):	40%
VISUAL BRIGHTNESS:	Good
COLOUR RECOGNITION:	Limited

laser safety spectacle R17T1E02

WAVELENGTH	OD	OPERATING MODE / TESTED PROTECTION LEVEL
180 - 315	(OD10+)	D LB10 + IR LB5 + M LB5Y
>315 - 532	(OD8+)	D LB7 + IR LB8 + M LB8Y