

laservision

TTS.M7P06.300x On-The-Table-System END



Articlenumber: TTSM7P063001
GTIN: 4050369058866
Unit: 1 Stück
Weight incl. packaging 0,00 kg

Highlights

The smallest start or end module of this system (TTS.M7P06.3001) is 300 mm long and can only be connected to other modules of this system on one side. It forms a nice finish to your new shielding and can be placed with the free end directly on the modules of the other systems (basic system and foldable edge system). The height of the system with 306 mm matches the other systems. Our barrier material M7P06 is built into this module for protection.

COLOUR:	black
PROPERTIES:	stable standing, standard plate material M7P06, freely selectable number of modules, both-sides usable
PROTECTION CLASS / NORM:	EN 60825-4
PROTECTION RANGE:	near infrared, Infrared, visible, ultraviolett

WAVELENGTH	OD	OPERATING MODE / TESTED PROTECTION LEVEL
180 - 315	–	D AB9 + IR AB4 + M AB6Y
>315 - 1050	–	D AB8 + IR AB9 + M AB10
>1050 - 1400	–	D AB7 + IR AB9 + M AB10
>1400 - 25000	–	D AB5

DIN EN 60825-4

780-1400nm | 960 kW/m² | T2 | t_{max} = 210s

9000-11000nm | 615 kW/m² | T2 | t_{max} = 105s