laservision

TTS.POST1.1001 standard column with M6 thread



Articlenumber: TTSPOST11001 GTIN: 4050369056534

Unit: 1 Stück

Weight incl. packaging 0,00 kg Weight excl. packaging: 0,26 kg

Highlights

The standard column TTS.POST1.1001 is mounted directly in the drilling grid of the OT using an M6 threaded pin. It has a total height of 309 mm and is suitable for holding a maximum of 3 laser protection plates (TTS.M7P06.100x) with a height of 306 mm. A plastic cap at the top minimizes the risk of injury. The ability to rotate around the central M6 pin enables great flexibility in laser protection barriers. Customerspecific panel lengths can be ordered for superstructures that are not along the grid.

COLOUR:	black
PROPERTIES:	up to 3 modules insertable, stable standing
PROTECTION CLASS / NORM:	EN 60825-4
PROTECTION RANGE:	near infrared, Infrared

 $\textbf{LASERVISION GmbH \& Co.KG} \mid \textbf{W\"{u}rzburger Str. 152}, \textbf{D-90766 F\"{u}rth} \mid \textbf{T +49 911 9736 8100} \mid \textbf{E} \ \text{info@lvg.com} \mid \textbf{I} \ \textbf{uvex-laservision.de}$